



# TECHNICAL SUPPORT PRODUCTS

Product catalogue



Subject to technical alterations.

KLINGER Industrial Products India Pvt. Ltd. #6 Tarana, 1st Floor,  
GoodEarth Malhar, Kambipura, Kengeri, Bengaluru 560074, Karnataka,  
India. Tel +91 8618523021 / +91 80 2990 9572 / e-mail: info@klinger.in

[www.klinger.in](http://www.klinger.in)

# PENETRATING OIL

KLINGER penetrating oil has been specifically formulated to loosen rusted and seized nuts, bolts and fittings. Instantly and effectively penetrating rust, dirt and scale leaving them with a clean film and reducing assembly time.



# NICKEL ANTI-SEIZE

KLINGER Nickel anti-seize compound is designed to prevent seizing, galling and prevent corrosion in nuts and bolts in temperatures up to 1300°C. The unique formulation allows for firmer and more accurate tightening and torqueing of threaded connections and mating surfaces, while enabling easier loosing.

The product protects against galvanic and electrolytic corrosion and is suitable for all types of steel including austenitic stainless steels.

KLINGER Nickel anti-seize has a coefficient of friction of 0.11

Nickel anti-seize can be used where copper-based compounds are undesirable.

Conforms to US Military specification – MIL-A-907E.



# CHAIN & LINKAGE SPRAY

KLINGER Chain and linkage spray is a low friction soluble molybdenum based lubricant. The formulation resists fling-off and is highly water resistant. The spray penetrates deep into linkages and remains adhered to surfaces in inaccessible places to give long-lasting protection under demanding conditions. The 360° valve technology allows spraying at all angles, including upside down.



# SUPER PROTECTIVE FILM

KLINGER Super Protective Film is a ultra-thin spray film that can be applied to any surface.

The film, once dry, will protect circuit boards and electrical components and exposed connections. The spray repels moisture from brass hinges and hardware. The Protective film seals steel surfaces and protects leaking skylights. The Coverage is 1-2m<sup>2</sup> per can depending on spray thickness. UV stabilized for 12-24 months and DI-Electric strength in excess of 1000V.





Subject to technical alterations.  
KLINGER Industrial Products India Pvt. Ltd. #6 Tarana, 1st Floor, GoodEarth Malhar, Kambipura, Kengeri, Bengaluru  
560074, Karnataka, India. Tel +91 8618523021 / +91 80 2990 9572 / e-mail: info@klinger.in

[www.klinger.in](http://www.klinger.in)