

BOILER

Flexible Metal Hoses



Profile of the boiler hoses is similar to solar hoses, but the wall thickness is larger.

These hoses have a longer life at high pressures due to their high wall thickness.

It is used in the manufacture of heat exchangers, especially boilers.

Advantages

- » Large surface areas
- » High heat transfer efficiency
- » Can be supplied in one long piece lengths
- » Heating surface without calcification for heating
- » High acid and corrosion resistance with its stainless steel body
- » Can be installed easily different boiler type with its flexible body

Applications

- » Boiler systems
- » Heat Pumps
- » Hot & Cold water pipelines




DESIGN VALUES

Without Braid	MH 211 K
Hose Material	316L
Fittings Material	304, 316L
Working Pressure	0-10 barg
Sizes	DN20-DN40



211 K



DN		Type	d1	d2	Tolerance	Working Pressure at 20°C	Surface Area	Weight	Length
mm	inch		mm	mm	mm	barg	m ² /m	kg/m	m
20	3/4"	MH 211 K	20,4	26,7	± 0,3	16	0,130	0,305	10-100
25	1"	MH 211 K	25,4	31,9	± 0,4	12	0,191	0,382	10-100
32	1 1/4"	MH 211 K	34,5	41,1	± 0,4	10	0,221	0,553	10-100
40	1 1/2"	MH 211 K	40,5	49,6	± 0,4	10	0,255	0,800	10-100



Subject to technical alterations.

KLINGER Industrial Products India Pvt. Ltd. #6 Tarana, 1st Floor,
GoodEarth Malhar, Kambipura, Kengeri, Bengaluru 560074, Karnataka,
India. Tel +91 8618523021 / +91 80 2990 9572 / e-mail: info@klinger.in