




Polystrat LC38-40 is Noise absorbing shim for disc brakes

Hard Steel shim with temperature- and pressure resistant rubber coating. One-sided adhesive coating and perfect damping performance



Basis composition NBR/Carbon Steel/NBR			Roll	ROLL LENGTH up-to 500 m
Color	Black - Other per request	Width Up-to 500 mm		Up-to 500 mm
Composite and tolerances	Rubber, NBR Cold rolled carbon steel PS-adhesive, acrylic Release paper, siliconized Total without release paper		0.025 ± 0.00 0.380 ± 0.02 0.080 ± 0.01 0.100 ± 0.02 0.485 ± 0.03	0 mm 0 mm 0 mm

Industry / Application


Engines / Compressors / Brake systems / Automotive

Tvi	oical	tech	mica	l data	and Pro	perties	for	KLINGER®	Polv	rstrat

Max. creep relaxation	ASTM F38	%	12
Adhesive bonding strength to the steel plate	SAFT	°C	100 - 150
	To steel plate	N/mm	≥ 3
Bonding conditions	Shim connection		
	Temperature of back plate	°C	≥ 20
	Pressure	MPa	2-3
	Pressure time	S	5
Rubber hardness	Shore A ISO 7619-1		70-75
Compression	ISO 815-1	%	25-27
Corrosion	EKB 1102	Grade	0
Storage life (Higher storage temperature and or longer storage time may cause a quality decrease of the product)	DIN 7716	Months	24



Damping characteristics



Damping characteristics:

Is used in Q-Control when evaluating the material responses to dynamic loading conditions. Materials with high damping coefficients are used in applications of shock absorption, vibration control, noise reduction, and dissipating increased heat.

All information is based on years of experience in production and operation of sealing elements. However, in view of the wide variety of possible installation and operating conditions one cannot draw final conclusions in all application cases regarding the behaviour in gasket joint. The data may not, therefore, be used to support any warranty claims. This edition cancels all previous issues. Subject to change without notice.

